

AVAILABLE OPTIONS BY SERIES

OPTIONS	SERIES									OPTION	SERIES									
	R	SD	S	M	L	K	ES2	AS	R		SD	S	M	L	K	ES2	AS			
Enclosure Type 4 Standard	NEMA Type 4X									Speed Control	12Vdc									
	NEMA Type 6								24Vdc											
	NEMA Type 7								24Vac											
	NEMA Type 4 & 7								115Vac											
									230Vac											
Motor Voltage 115Vac Standard	115Vac Ext'ed Duty								Timer	12Vdc										
	24Vac									24Vdc										
	24Vdc									24Vac										
	12Vdc									115Vac										
	208Vac/1ph/60Hz									230Vac										
	230Vac/1Ph/60Hz								Multi-Position, Vac	Three Position										
	230Vac/3Ph									Four Position										
	380Vac3Ph/50Hz									Multi-Position, Vdc	Three Position									
460Vac/3Ph								Four Position												
Coating	Epoxy Coating								Position Indicator	Diamond										
	Anodize									ICI Dome										
Auxiliary Switches	One								Light Indication	4-20mA Transmitter										
	Two									Three Position										
	Three										3	3	3	3	3					
	Four																			
Proximity Switches	Limit								Power Supply	115Vac or 230Vac										
Declutching	NEMA Type 4				1	1	1		Two Conduit	NEMA Type 4										
Man-O-Ride	NEMA Type 7								Entries	NEMA Type 7										
Brake, Power On	12Vdc								Mechanical Stop											
	24Vdc									Breather										
	24Vac										Heater									
	115Vac							1				1	Heater & Stat.							
	230Vac											1		1	Torque Sensor					
												Multi-Turn								
Brake, Power Off	12Vdc								Reversing	DC Voltage										
	24Vdc									Contactor	3 Ph. Motors									
	24Vac										Transformer									
	115Vac												2 Wire Control	12Vdc						
	230Vac											Remote Local Control		24Vdc						
								24Vac												
Potentiometer	1K, Single Turn									115Vac										
	1K, Single Turn, Dual										230Vac									
	1K, 3:1 Ratio												230Vac							
	1K, 0 to 135 ohm											230Vac								
	1K, Ten Turn								230Vac											
	5K, Single Turn									230Vac										
Positioner	12Vdc & 24Vdc	2									Remote Local Control									
	24Vac												230Vac							
	115Vac	2										230Vac								
	230Vac	2							230Vac											
	115Vac High Resolution									230Vac										
	0-135 ohm													230Vac						

1. Standard equipment
2. Assembled in SD enclosure
3. Third party vendor